

Product name: High temperature grease

Revision date: March 24, 2024

Requirements of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Original preparation date: July 18, 2014

SDS number: MAXTOP 20240324 Version: A2

Material Safety Data Sheet

Part 1 Chemicals and Company Identification

Product Identification

Product Name: High temperature grease

Product model: 1# , 2# , 3#

Product Type: Paste

Recommended use of the product and restrictions on use

Recommended use: High temperature grease is a lubricating product designed to withstand high temperature environments. It is usually made of synthetic oil or high temperature base oil and high temperature thickener (such as polyurea, lithium composite, silicone, polytetrafluoroethylene, etc.), and has excellent thermal stability, oxidation stability and shear resistance. Its main function is to form a stable lubricating film on the friction surface under high temperature conditions, effectively reduce wear, prevent adhesion, extend the service life of equipment, and maintain good lubrication effect without dripping or carbonization. High temperature grease is suitable for high temperature bearings, dryers, hot air circulation fans, electric furnace transmission parts, metallurgical rolling mill bearings, kiln car bearings, injection molding machines, ovens, hot presses and other equipment. It has a wide range of application value in high temperature industrial fields such as

Product name: High temperature grease

Revision Date: March 24, 2024

SDS Number: MAXTOP 20240324

metallurgy, building materials, glass, ceramics, textiles, plastics, aviation, steel, and automobile manufacturing. It is particularly suitable for key parts that require high temperature and long-term lubrication and reduce maintenance frequency.

Restrictions on Use: This product is for use only as recommended without prior written permission from the supplier.

Corporate identity

Manufacturer: Chengdu Maxtor New Energy Lubricating Materials Co., Ltd.

Address: No. 138 Guanshan Road, Shuangliu District, Chengdu, China (Sichuan)

Pilot Free Trade Zone

Email: maxtop@maxtop-oil.com

Fax number: 028-85857666

Emergency consultation telephone number:

Tel: 028-85857666

Emergency phone number: 028-85857666

Section 2. Hazards identification

Emergency Overview:

Liquid, flammable when exposed to open flame. Harmful to humans by inhalation. Harmful to aquatic life.

GHS Hazard Classification:

Aspiration hazard Category 1: H304

Long-term aquatic hazards - chronic Category 3: H412

Causes skin irritation Category 3: H4 15

Label elements:

Hazard pictograms:



Signal Word: Danger

Hazard Statements: H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

H415 Causes skin irritation

Precautionary Statements:

Precautions: P273 Avoid release to the environment.

Incident Response: P301+P310+P331 If swallowed, immediately call a poison center or doctor. Do not induce vomiting.

Secure Storage: P405 Closed storage.

Disposal: P501 Dispose of contents and container in accordance with local, national and international regulations.

Health and Environmental Hazards: See Sections 11 and 12.

Other hazards: Prolonged or repeated contact may cause skin dryness and irritation.

Section 3 Product composition and ingredient information

This product is a saponification product of lubricating base oil, stearic acid, dodecyl

stearic acid, lithium hydroxide and composite additives , and the composition

contents are all in weight percentage.

Product/ingredient name	Identification code	Content (WT%)	Hazard Type
Lubricant base oil	64741-96-4	88.2	H304
Stearic acid	57-11-4	1.5	No clear hazard classification, low toxicity
Dodecyl Hydroxystearic Acid	106-14-9	7.0	No GHS hazard label
Lithium hydroxide	1310-66-3	1.8	H315
Compound Additives	-	1.5	H41 2

Note: According to EU Regulation (EC) No 1272/2008 [CLP] Annex VI Nota L applies to the base oils of this product. If it can be shown that the substance contains less than 3% of DMSO extract as determined by IP346, it does not need to be classified as a carcinogen.

Section 4. First aid measures

first aid:

suck Inhalation: Leave the scene immediately to fresh air and keep the respiratory tract open. If you feel dizzy, nauseous, or
If unconscious, seek medical attention immediately.

Skin contact: Take off contaminated clothing and wash the contaminated part with a soap dish and plenty of running water. If the product is injected into the subcutaneous tissue or any part of the human body, regardless of the appearance or size of the wound, the patient must be sent to the hospital for surgical examination and treatment immediately.

Eye contact: Immediately open the upper and lower eyelids and rinse with running water or saline. If persistent irritation occurs, seek medical attention.

Food Adverse symptoms may include nausea or vomiting, diarrhea. Do not induce vomiting unless directed to do so by a medical professional.

If the symptoms are severe, go to the hospital immediately for diagnosis and treatment, and take vomiting or other rescue measures under the guidance of the doctor.

Acute and delayed effects and most important symptoms and effects (overexposure):

suck Inhalation: Inhalation of oil mist or vapor at elevated temperatures may cause respiratory irritation.

Skin contact: Adverse symptoms may include irritation, dryness, and cracking.

Eye Contact: Slightly irritating.

Special note to doctors: Due to the low viscosity of the product, there is a risk of inhalation hazard if it enters the lungs, and symptomatic treatment should be given.

Section 5 Firefighting measures

Fire extinguishing agent:

Foam, dry powder, carbon dioxide, sand and soil can be used to extinguish the fire. Do not use water as a fire extinguishing agent.

Special hazards:

The flash point of this product is greater than 75°C, and it may burn when exposed to open flame, high heat or contact with oxidants. Incomplete combustion may produce harmful combustion products such as CO, H₂S, sulfide, solid suspended particles and complex combustion mixtures.

Fire extinguishing precautions and protective measures

Firefighting method: Firefighters must wear gas masks and full-body fire suits and fight fires in the upwind direction. Move containers away from the fire scene to an open area as much as possible. If the container in the fire scene changes color or sounds from the safety pressure relief device, it must be evacuated immediately.

Protection of firefighters Special firefighting equipment: Firefighters should wear appropriate protective gear and self-contained breathing apparatus (SCBA) with positive pressure mode on the front. Firefighter clothing that meets European standard EN 469 (including helmet, protective boots and gloves) provides basic protection for chemical incidents.

Section 6. Emergency measures for release

Personal protection measures, protective equipment and emergency response procedures:

For non-emergency responders:

Avoid breathing vapor or mist. Keep non-involved personnel away from the spill area. Any action, except for small spills, should be evaluated and advised by a professional emergency manager. If a large spill occurs, alert downwind residents. Limited spills in the open air, especially vapors, will dissipate quickly and reduce hazardous concentrations.

For emergency responders:

Small leak: Ordinary antistatic work clothes can be used.

Large spills: Use full chemical, heat and corrosion resistant gear. Note: PVA gloves are not waterproof and are not suitable for emergency use. Wear a hard hat,

anti-static and non-slip safety shoes or boots, goggles or a mask to prevent possible splashes or contact with eyes.

Respiratory protection: Wear a half-mask or full-face respirator that can filter organic vapors (suitable for hydrogen sulfide). Choose a self-contained breathing apparatus (SCBA) based on the extent of the leak and the foreseeable exposure. If the risk cannot be fully assessed or there is a possibility of hypoxia, only SCBA should be used.

Environmental protection measures:

If a large amount of leakage occurs, it may be harmful to the environment. If the product has caused environmental pollution (sewers, waterways, soil or air), the relevant departments should be notified promptly. Prevent the leakage from entering sewers, surface water and groundwater. If necessary, build a bank with dry soil, sand or similar non-combustible materials. If soil contamination occurs, the contaminated soil should be removed and disposed of in accordance with local regulations.

In the event of a small spill in a closed water area (i.e. a port), a container with a floating barrier or other device and absorbent should be used to absorb the spilled product. If possible, a large spill in open water should be controlled by a floating barrier or other mechanical device. Otherwise, the spread of the spill should be controlled.

Containment and cleanup methods of leaked chemicals and the materials used:

Small leakage: Collect the leaked liquid in a sealed container as much as

possible, and absorb the residual liquid with sand, activated carbon or other inert materials. You can also use an emulsion made of a non-flammable dispersant to scrub it, and the washing liquid should be disposed of harmlessly.

Large-scale leakage: Report the situation to relevant departments according to the risk level. Build dikes or dig pits to contain the leakage. Use pumps to transfer the leakage to sealed containers and recycle or transport it to waste disposal sites for disposal.

Section 7. Handling and Storage

Operational Disposal:

The place where this product is used should meet the requirements of fire protection design specifications, and excessive oil mist should be avoided during operation. Operators should receive fire safety training and be equipped with necessary labor protection equipment to avoid inhaling oil mist. Production equipment should eliminate leakage to avoid the risk of slipping.

store:

This product should be stored in a sealed, cool, dry and ventilated place, away from open flames, high temperature heat sources, strong oxidants and flammable materials, and avoid mixing with water, impurities and other foreign matter. The storage area should be equipped with necessary fire-fighting equipment and leakage emergency treatment equipment. The storage container is recommended to be container material, or use low-carbon steel or stainless steel container lining. Some products may still remain in the empty container, so do not heat, cut or weld

with open flame.

Section 8. Exposure controls and personal protection

Occupational exposure limits:

When oil mist and smoke appear, the following standards are recommended:

AFS (Sweden, 2/2018) stipulates that the short-term exposure allowable concentration (STEL) is $3\text{mg}/\text{m}^3$ 15min: the cumulative time average allowable concentration (TWA) is $1\text{mg}/\text{m}^3$ 8h.

Engineering control methods:

Forced ventilation and local exhaust can reduce airborne exposure concentrations. Use oil-resistant materials for operating devices. Store under recommended conditions. If heating is required, use temperature control devices to avoid overheating.

Personal protective equipment:

Respiratory protection: If the product needs to be heated manually, a respirator with filter A1P2 or A2P2 should be selected. If it is an automatic production line with good ventilation facilities, a respirator is not required.

Hand protection: Wear oil-resistant protective gloves (such as nitrile rubber), high-quality PVC.

Eye Protection: If splashing is possible, wear safety glasses.

Skin protection: If skin contact occurs, wear protective clothing and wash contaminated protective clothing before reuse.

Hygiene measures: Maintain good personal hygiene habits, such as washing

hands after handling this product, and eating, drinking or smoking.

Wash hands before smoking. Wash work clothes and protective equipment regularly to remove pollutants. Discard contaminated clothing and shoes that cannot be washed. Develop good living habits.

Section 9. Physical and Chemical Properties

model project	1#	2#	3#
Appearance	Blue smooth uniform ointment		
Working cone penetration/(0.1mm)	310~340	265~295	220~250
Dropping point/°C No less than	260	260	260
Corrosion (T2 _{copper} sheet, 100°C, 24h)	20 Copper sheet has no green or black change		
Water loss (38°C, 1h), % (mass fraction) No more than	5		
Change rate of extended working cone penetration 0.1mm (100,000 times), % No more than	15	20	20
Leakage (104°C, 6h), g No more than	2.5		
Corrosion resistance (52°C, 48h)	qualified		
Evaporation amount (180°C, 1h), % (mass fraction) No more than	5		
Oxidation stability (99°C, 100h, 0.770MAa) not more than	0.070		
Similar viscosity (-10°C, 10s), Pa.s No more than	500	800	1200
Bearing life (149°C), h Not less than	400		

Section 10. Stability and Reactivity

Stability: Under normal conditions this product is stable.

Possibility of hazardous reactions: None under normal conditions of storage and

use.

Conditions to avoid: Open flames, high heat sources.

Incompatible Materials: Strong oxidizing agents.

Hazardous decomposition products: Incomplete combustion may produce CO, H₂S, sulfides, solid suspended particles and complex combustion mixtures.

Section 11 Toxicological information

Acute Toxicity: No known significant effects or significant hazards.

Skin Irritation or Corrosion: No known significant effects or significant hazards.

Eye Irritation or Corrosion: No known significant effects or significant hazards.

Respiratory or Skin Sensitization: No known significant effects or significant hazards.

Germ Cell Mutagenicity: No known significant effects or significant hazards.

Carcinogenicity: Product is not a carcinogen. There are no known significant effects or significant hazards from long-term exposure.

Reproductive Toxicity: No known significant effects or significant hazards.

Specific target organ toxicity - single exposure: No known significant effects or significant hazards.

Specific target organ toxicity - repeated exposure: No known significant effects or significant hazards.

Aspiration Hazard: Category 1 aspiration hazard.

Section 12. Ecological information

Ecotoxicity: This product may produce ecotoxicity under conditions of long-term

penetration and long-term large-scale accumulation.

Persistence and Degradability: Components of this product are not readily

biodegradable and have the potential to bioaccumulate.

Bioaccumulative Potential: Has the potential to bioaccumulate.

Mobility in soil: This product is a non-volatile liquid. It will not produce oil vapor to affect the atmosphere in the natural environment. It has low water solubility and can migrate from water to land in a floating state. Once it enters the soil, it will be absorbed by soil particles and cannot flow.

Section 13. Disposal considerations

Waste nature: HW08 in the National Hazardous Waste List - Waste Mineral Oil

Waste chemicals: must comply with the local laws and regulations in use at the time. If possible, they should be handed over to institutions with relevant hazardous waste treatment qualifications for product recycling. It is recommended to use them as boiler fuel under controlled conditions, and to test the harmful substances in the exhaust gas produced by high-temperature combustion. For temporary storage of waste, sealed containers should be used to avoid light and necessary labels should be made.

Contaminated packaging: Contaminated packaging should be recycled.

Incineration or landfill should only be considered if recycling is not feasible.

Section 14. Transport Information

According to GB6944 "Classification and Product Name Numbering of Dangerous Goods" and GB12268 "List of Dangerous Goods": This product is not a dangerous

Product name: High temperature grease

Revision Date: March 24, 2024

SDS Number: MAXTOP 20240324

good.

United Nations Dangerous Goods Number (UN Number): None.

UN Hazard Classification: Not applicable.

Packing group: Not applicable.

Marine Pollutant (yes/no): No

Transportation precautions: The product should be transported safely and in a sealed container. Ensure that the transport personnel are aware of the disposal methods in case of accidents or leaks.

Section 15. Regulatory information

According to the European Union Safety, Health and Environment Regulation (EC) No. 1907/2006 (REACH), it complies with the requirements of the following national and regional chemical catalogs: IECSC (China Existing Chemical Substances Inventory), DSL (Canada), EINECS (EU), ENCS (Japan), KECI (Korea), PICCS (Philippines), TSCA (USA), AICS (Australia).

Section 16. Other Information

This product safety data sheet is developed based on current knowledge and applicable laws and regulations. It describes this product from the perspective of health, safety and environmental regulations. It is subject to revision based on updates to referenced standards and test data.

The data and recommendations provided in this product safety data sheet are only applicable to the specified use of this product. Chengdu Maxtor New Energy Lubricating Materials Co., Ltd. will not be held responsible for any damage or injury

Product name: High temperature grease

Revision Date: March 24, 2024

SDS Number: MAXTOP 20240324

caused by failure to follow the recommendations other than the specified use.

Users who purchase this product can obtain other information through the sales department and technical service department.