

Low temperature thermal fluid (MTLT-75)

● Performance Overview

Maxtop low temperature heat transfer fluid(MTLT-75) uses ultra-low pour point and high stability synthetic materials as base oil, adds self-developed MAXTOP heat transfer oil composite additives, uses multiple patented formula technologies, and is developed through multiple self-developed ultra-long-term anti-coking test technologies that are both low temperature, high temperature and oxidized. It has ultra-low low-temperature fluidity, no semi-solid or solid matter precipitates at low temperatures, smooth low-temperature fluidity, and no obvious viscosity increase at low temperatures.

● Features

01

Good low-temperature fluidity, less resistance to cold start and operation at low temperatures.

03

Excellent self-cleaning properties. If used correctly, it will not produce high or low temperature deposits in the system, will not form glue, will not block the heat exchanger, and will not increase energy consumption.

05

When operating at low temperatures, no deposits will be generated in the oil, which will not affect the heat transfer of the system.

02

When running at high temperatures, the product quality is stable

04

The energy-saving effect is remarkable, and the service life is very long.

06

Comprehensively protect the metal surface from rust, reduce evaporation loss and oil replenishment, and ensure stable pressure during system operation.



● Application Scenario

MTLT-75 is mainly used for heat transfer in low temperature working environment: the use temperature range is -70°C to 230°C, and it is better to use it in a closed system. If it is used in an open system, the interface temperature in contact with air should be less than 60°C. Under the process conditions of high temperature, low temperature and oxidation, the stability of this product is particularly outstanding.



Typical data of low temperature thermal fluid (MTLT-75)

Project	Quality indicators
Appearance	Colorless transparent liquid
Density (20°C)/(Kg/m ³)	756.3
Moisture (mg/kg), %	41
Flash point (open), °C	102
Autoignition point°C	244
Pour point, not more than °C	-75
Distillation range °C	207~222
Acid value mgKOH/g	0.01
Carbon residue (mass fraction), %	0.01
Sulfur content mg/kg	0.55
Chlorine content mg/kg	1
Copper corrosion (100°C, 3h), level	1a
Thermal expansion coefficient (1/°C)	0.0015
Best recommended operating temperature °C	-70~230
Maximum liquid film temperature °C	245
Kinematic viscosity mm ² /s 40°C	1.51
Kinematic viscosity mm ² /s	20.15 (-50°C)
Low temperature pumpability/°C mm ² /s	86.9 (-70°C)
The temperature without low-temperature precipitation is less than °C	-80
Thermal oxidation stability (high temperature °C*oxidation °C*time h) passed	210*100*480

● The above data are typical values of current products. The data of each batch of products in the future may fluctuate within the allowable range of Maxtor quality standards.

